


Şafak Serisi

İzoleli Kablo Yüksükleri Alman Renk Normu (DIN 46228)



Standart : DIN 46228
Malzeme : Bakır (E-Cu), Kalay kaplı
İzolasyon : Naylon
Çalışma Sıcaklığı : Maksimum 105° 600 Volt

Ürün Kodu	Renk	Kablo Kesiti mm ²	Ebatlar (mm)							Ambalaj Miktarı (Ad)	Koli Miktarı (Ad)	Ambalaj Ağırlığı (-gr)
			F	L	W	B	D	C				
UY-2005 E		Turuncu	0,50 mm ²	8,0	14,0	2,6	6,0	1,3	1,0	500	60.000	64
UY-2007 E		Beyaz	0,75 mm ²	8,0	14,0	2,8	6,3	1,5	1,2	500	60.000	72
UY-2010 E		Sarı	1,00 mm ²	8,0	14,0	3,0	6,3	1,7	1,4	500	60.000	75
UY-2015 E		Kırmızı	1,50 mm ²	8,0	14,0	3,5	6,3	2,0	1,7	500	30.000	108
UY-2025 E		Mavi	2,50 mm ²	8,0	15,0	4,2	7,4	2,5	2,2	500	30.000	133
UY-2040 E		Gri	4,00 mm ²	10,0	17,0	4,8	7,4	3,2	2,8	250	15.000	119
UY-2060 E		Siyah	6,00 mm ²	12,0	20,0	6,3	8,5	3,9	3,5	250	12.500	179
UY-2100 E		Bej	10,00 mm ²	12,0	22,0	7,6	8,8	4,9	4,5	100	6.000	109
UY-2160 E		Yeşil	16,00 mm ²	12,0	24,0	8,8	10,0	6,2	5,8	100	5.000	138
UY-2250 E		Kahve	25,00 mm ²	16,0	28,0	11,2	12,0	7,7	7,3	50	2.500	125
UY-2350 E		Bej	35,00 mm ²	16,0	30,0	12,7	14,0	8,7	8,3	50	2.500	140
UY-2500 E		Zeytuni	50,00 mm ²	20,0	36,0	15,0	16,0	10,9	10,3	50	2.500	168