











Şafak Serisi İzoleli Çift Girişli Kablo Yüksükleri (DIN 46228)



Standart : DIN 46228
Malzeme : Bakır (E-Cu), Kalay kaplı
İzolasyon : Naylon
Çalışma Sıcaklığı : Maksimum 105° 600 Volt

Ürün Kodu	Renk	Kablo Kesiti mm ²	Ebatlar (mm)						Ambalaj Miktarı (Ad)	Koli Miktarı (Ad)	Ambalaj Ağırlığı (-gr)
			F	L	W	B	D	C			
UY-23005 E	 Beyaz	2 x 0,50 mm ²	8,0	14,5	5,0	6,5	1,8	1,5	500	30.000	107
UY-23007 E	 Mavi	2 x 0,75 mm ²	8,0	14,7	5,5	6,7	2,1	1,8	500	30.000	121
UY-23010 E	 Kırmızı	2 x 1,00 mm ²	8,0	15,1	5,5	7,1	2,4	2,1	500	30.000	137
UY-23015 E	 Siyah	2 x 1,50 mm ²	8,0	15,5	6,4	7,5	2,6	2,3	500	25.000	164
UY-23025 E	 Gri	2 x 2,50 mm ²	10,0	18,5	8,0	8,5	3,3	2,9	250	12.500	137
UY-23040 E	 Turuncu	2 x 4,00 mm ²	12,0	23,1	8,8	11,1	4,2	3,8	100	6.000	98
UY-23060 E	 Yeşil	2 x 6,00 mm ²	14,0	26,1	9,5	12,1	5,3	4,9	100	5.000	149
UY-23100 E	 Kahve	2 x 10,00 mm ²	14,0	26,6	12,6	12,6	6,9	6,5	50	3.000	108
UY-23160 E	 Bej	2 x 16,00 mm ²	14,0	31,3	19,0	17,3	8,7	8,3	50	2.500	56