















Şafak Serisi İzoleli Kablo Yüksükleri *Fransız Renk Normu (DIN 46228)*



Standart : DIN 46228
Malzeme : Bakır (E-Cu), Kalay kaplı
İzolasyon : Naylon
Çalışma Sıcaklığı : Maksimum 105° 600 Volt

Ürün Kodu	Renk	Kablo Kesiti mm ²	Ebatlar (mm)							Ambalaj Miktarı (Ad)	Koli Miktarı (Ad)	Ambalaj Ağırlığı (~gr)
			F	L	W	B	D	C				
UY-3005 E	 Beyaz	0,50 mm²	8,0	14,0	2,6	6,0	1,3	1,0	500	60.000	64	
UY-3007 E	 Mavi	0,75 mm²	8,0	14,0	2,8	6,3	1,5	1,2	500	60.000	72	
UY-3010 E	 Kırmızı	1,00 mm²	8,0	14,0	3,0	6,3	1,7	1,4	500	60.000	75	
UY-3015 E	 Siyah	1,50 mm²	8,0	14,0	3,5	6,3	2,0	1,7	500	30.000	108	
UY-3025 E	 Gri	2,50 mm²	8,0	15,0	4,2	7,4	2,5	2,2	500	30.000	133	
UY-3040 E	 Turuncu	4,00 mm²	10,0	17,0	4,8	7,4	3,2	2,8	250	15.000	119	
UY-3060 E	 Yeşil	6,00 mm²	12,0	20,0	6,3	8,5	3,9	3,5	250	12.500	177	
UY-3100 E	 Kahve	10,00 mm²	12,0	22,0	7,6	8,8	4,9	4,5	100	6.000	109	
UY-3160 E	 Fildişi	16,00 mm²	12,0	24,0	8,8	10,0	6,2	5,8	100	5.000	138	
UY-3250 E	 Siyah	25,00 mm²	16,0	28,0	11,2	12,0	7,7	7,3	50	2.500	125	
UY-3350 E	 Kırmızı	35,00 mm²	16,0	30,0	12,7	14,0	8,7	8,3	50	2.500	141	
UY-3500 E	 Mavi	50,00 mm²	20,0	36,0	15,0	16,0	10,9	10,3	50	2.500	168	
UY-3700 E	 Sarı	70,00 mm²	20,0	37,0	16,0	17,0	14,3	13,5	50	2.500	270	